



RECOMMENDED P.C.B LAYOUT

Specification

Insulator Material: Polyesetr, UL94V-0

Standard: P.B.T or PA6T

Contact Material: Brass

Contact plated: Gold Over Nickel

Poles: 2~40P

Current Rating : 3Amp

Contact Resistance: 20 Milliohms Max

Insulation Resistance : 1000MΩ Min.

Dielectric withstanding Voltage: AC 500V

Operation Temperature : -40°C -- +105°C

核准:	日期:	C km t w 深圳市灿科盟实业有限公司 CHANKLEMENT INDUSTRYCO., LTD																				
业务:	日期:																					
制图:	日期:	品名规格: 210R-1*XP(6.0/2.5/1.5/3.0)																				
L Y F	2009-12-28	客户料号: /																				
<table border="1"> <tr> <td>X.X</td> <td>±0.2</td> </tr> <tr> <td>X.XX</td> <td>±0.10</td> </tr> <tr> <td>X.XXX</td> <td>±0.050</td> </tr> </table>	X.X	±0.2	X.XX	±0.10	X.XXX	±0.050	未注公差表	<table border="1"> <tr> <td>单位</td> <td>mm</td> <td>比例</td> <td>/</td> <td>图</td> <td>Φ</td> <td>锥</td> </tr> <tr> <td>图纸编号:</td> <td>Ckmtw-201-00007</td> <td>版本</td> <td>A</td> <td></td> <td></td> <td></td> </tr> </table>	单位	mm	比例	/	图	Φ	锥	图纸编号:	Ckmtw-201-00007	版本	A			
X.X	±0.2																					
X.XX	±0.10																					
X.XXX	±0.050																					
单位	mm	比例	/	图	Φ	锥																
图纸编号:	Ckmtw-201-00007	版本	A																			